









UNDERSTANDING THE 7 FIGURE CAM REFERENCE						
1st Number	2nd Number	3rd Number	4th & 5th Number		6th & 7th Number	
CAM PIERCING	CAM THICKNESS	SHAPE	DIMENSION 'A' IN 0.4mm INCREMENTS SEE TABLE BELOW		DIMENSION 'B' IN MILLIMETRES (mm)	
<p>6 = 8 mm sq</p>  <p>FOR STANDARD CAMLOCK IF DIFFERENT WE WILL SPECIFY</p>	3 = 2.8mm	0	 <p>A ≥ 6mm</p>			
		1	 <p>A ≤ 6mm</p>			
		2	4th & 5th	SIZE	CAM	W =
		3	No.s	IN		
		mm	TYPE			
<p>M =</p>  <p>FOR MINI CAMLOCKS</p>	2 = 2mm	4	02	0.8	M	12.7
		5	04	1.6	T	14.3
		6	08	3.2	6	15.5
		7	12	4.8		
		8	14	5.6		
		9	16	6.4		
			20	7.9		
			24	9.5		
			28	11.1		
			32	12.7		
<p>T = 6.5 mm sq</p>  <p>FOR OFFICE FURNITURE &amp; SOME CAMLOCKS</p>		 <p>EXAMPLE: CAM 6341620</p> <p>STAR PIERCED 2.8mm CRANKED 'B' = 20mm 'A' = 6.4mm CRANK</p>				
		<p>NOT ALL CAM VARIATIONS MAY BE AVAILABLE, REFER TO PAGE STANDARD CAMS</p>				